Patent claims

1. A component (2), in particular a sun visor (2) that is designed for use in a vehicle, the component (2) comprising a structural part (3) and a cover element (1), the cover element (1) being connected to the structural part (3) by means of a removable connection, characterized in that a connecting movement (26) of the cover element (1) relative to the structural part (3) is provided to produce the connection, in a direction (25) substantially tangential to at least one main extension direction (250) of the cover element (1).

2. The component (2) as claimed in claim 1, characterized in that the cover element (1) has at least one main extension direction (250), substantially in a plane (240) and in that the connecting movement (26) is carried out substantially in the plane (240).

3. The component (2) as claimed in claim 1, characterized in that the cover element (1) has at least one main extension direction (250), substantially in a cylindrical peripheral surface and in that the connecting movement (26) is substantially carried out in the cylindrical peripheral surface.

4. The component (2) as claimed in one of the preceding claims, characterized in that at least one first sliding element (16, 17, 18) of the structural part (3) or of the cover element (1) is arranged in the plane (240) or in the cylindrical peripheral surface.

5. The component (2) as claimed in one of the preceding claims, characterized in that the at least one first sliding element (16, 17, 18) cooperates with at least one second sliding element (19, 20, 21) for

locking the cover element (1) relative to the structural part (3), at least relative to a movement perpendicular to the plane (240) or to the cylindrical peripheral surface.

6. The component (2) as claimed in one of the preceding claims, characterized in that a snap-in connection (22, 23) is provided between the cover element (1) and the structural part (3) for locking the cover element (1) relative to the structural part (3), relative to a movement in the plane (240) or in the cylindrical peripheral surface.

7. The component (2) as claimed in one of the preceding claims, characterized in that the snap-in connection (22, 23) is reversibly removable.

8. The component (2) as claimed in one of the preceding claims, characterized in that the snap-in connection (22, 23) is only irreversibly removable.

9. The component (2) as claimed in one of the preceding claims, characterized in that the cover element (1) is provided in the manner of a frame.

10. The component (2) as claimed in one of the preceding claims, characterized in that the component (2) is a sun visor (2) with a mirror (10), the cover element (1) being provided at least for covering the edge region of the mirror (10).

11. A method for producing a component (2), in particular as claimed in one of the preceding claims, characterized in that the cover element (1) and the structural part (3) are arranged, in a first step, relative to one another such that the at least one first sliding element (16, 17, 18) and the at least one second sliding element (19, 20, 21) are at least

partially in contact and in that a connecting movement (26) of the cover element (1) relative to the structural part (3) is carried out, in a second step, in a direction substantially tangential to at least one main extension direction (250) of the cover element (1).